

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
24 February 2005 (24.02.2005)


PCT

(10) International Publication Number  
**WO 2005/016680 A3**

- (51) International Patent Classification<sup>7</sup>: **F02B 51/00**, F02M 27/00, 37/04
- (21) International Application Number: PCT/US2004/022818
- (22) International Filing Date: 15 July 2004 (15.07.2004)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:  
60/493,038 5 August 2003 (05.08.2003) US
- (71) Applicant (for all designated States except US): **COLORADO STATE UNIVERSITY RESEARCH FOUNDATION** [US/US]; P.O. Box 483, Ft. Collins, CO 80522 (US).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): **STANGLMAIER, Rudolf, H.** [MX/US]; 1916 Winterberry Way, Fort Collins, CO 80526 (US).
- (74) Agents: **KNEPPER, Bradley, M.** et al.; Sheridan Ross P.C., Suite 1200, 1560 Broadway, Denver, CO 80202-5141 (US).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: IMPROVED DRIVEABILITY AND REDUCED EMISSIONS DURING ENGINE START-UP



(57) Abstract: The present invention is related to improved drivability and reduced emissions during engine startup. In particular, fuel vapor is drawn from the fuel tank at or immediately prior to engine startup. The engine is then run using the fuel vapor, to at least partially warm the engine. Following the initial startup period, during which the engine becomes at least partially warm, liquid fuel is provided to the engine.



**Published:**

- *with international search report*
- *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments*

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

**(88) Date of publication of the international search report:**

19 May 2005